

# St. Leo

## DATA SHEET: ORIGINAL PIGMENTS – BALANCED MATTE

---

### PRODUCT DESCRIPTION:

This balanced composition of premium ingredients results in a durable matte finish with a rich colour profile for the enhancement of high-traffic interiors such as living rooms and corridors. Balanced Matte is waterborne and low-VOC with a thick and creamy consistency for easy application and a washable surface that ensures long-lasting beauty and atmosphere.

### PHYSICAL / CHEMICAL DATA

Usage:	Interior
Binder:	Acrylic copolymer dispersion
Gloss:	5 - matte
Drying time:	23°C 50% RH: 2 hours. Recoat after 6 hours.
Application Temp:	Min. +5°C
Humidity:	40-80% RH (65% RH is optimal)
Tools:	Brush, roller, spray
Dilution:	Water
Bases:	Base White, Base Clear
Package Sizes:	5L and 2.5L
Cleaning:	Soapy water
Storage:	Frost-free
MAL Code:	(1993): 00-1
EU VOC Limit Value:	(Cat. A/a) 30g/l. Contains Max 1g/l.

This declaration applies to the colour white. The figures may vary for other colours.

---

### DETAILS

#### Application:

Surfaces must be clean, dry, smooth and not transmit any loose particles. Untreated plaster, concrete and common construction boards must be primed before painting. Previously painted surfaces should be washed and degreased before painting. For best results, apply 1-2 coats of primer before applying 2 coats of paint. Stir the paint thoroughly before use. Drying time: approximately 6 hours at 23°C and 50% RH. Please follow full application instructions available at [stleointeriors.com](http://stleointeriors.com).

#### Coverage:

Approximately 6–8 M<sup>2</sup> / Litre.

#### Storage & Waste:

Always store in original packaging. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Storage temperature: Frost free. All paint residues and containers must be deposited at your local waste collection point.