

St. Leo

DATA SHEET: ORIGINAL PIGMENTS – VITAL SEMI MATTE

PRODUCT DESCRIPTION:

An intelligent recipe of sustainable matte acrylic creates a strong and scratch-resistant finish for active domestic and commercial interiors and kitchens. Vital Semi Matte creates a colourful interior environment is able to withstand the dynamics of everyday life.

PHYSICAL / CHEMICAL DATA

Usage:	Interior
Binder:	Acrylic copolymer dispersion
Gloss:	10 - matte
Drying time:	23°C 50% RH: 2 hours. Recoat after 6 hours
Application Temp:	Min. +5°C
Humidity:	40-80% RH (65% RH is optimal)
Tools:	Brush, roller, spray
Dilution:	Water
Bases:	Base White, Base Clear
Package Sizes:	5L and 2.5L
Cleaning:	Soapy water
Storage:	Frost-free
EU VOC Limit Value:	(Cat. A/a) 30g/l Contains Max 1g/l

This declaration applies to the colour white. The figures may vary for other colours.

DETAILS

Application:

Surfaces must be clean, dry, smooth and not transmit any loose particles.

Untreated plaster, concrete and common construction boards must be primed before painting. Previously painted surfaces should be washed and degreased before painting. For best results, apply 1-2 coats of primer before applying 2 coats of paint. Stir the paint thoroughly before use. Drying time: approximately 6 hours at 23°C and 50% RH. Please follow full application instructions available at stleointeriors.com.

Coverage:

Approximately 6–8 M2 / Litre.

Storage & Waste:

Always store in original packaging. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Storage temperature: Frost free. All paint residues and containers must be deposited at your local waste collection point.

CONTACT

+45 53740622

INFO@STLEOINTERIORS.COM

STLEOINTERIORS.COM