

St. Leo

DATA SHEET: ORIGINAL PIGMENTS – FORM FINISH SEMI GLOSS

PRODUCT DESCRIPTION:

A dynamic coating crafted to enhance the colour and durability of rough interior surfaces including woodwork, cabinets and pre-treated metal. Designed for convenient application using a roller or brush to achieve deep colour profiles and a semi-gloss appearance that is washable and resistant to scratches.

PHYSICAL / CHEMICAL DATA

Usage:	Wood and metal
Binder:	Acrylic copolymer dispersion
Gloss:	40 - semi gloss
Drying time:	at 23°C / 50% RH: 2 hours. Recoat after 12 hours.
Application Temp:	Min + 5°C. Max + 25°C
Humidity:	40-80% RH (65% RH optimal)
Tools:	Brush, roller, spray
Dilution:	Water. Max. 10%
Bases:	Base Clear, Base White
Package Sizes:	2.5L, 1L
Cleaning:	Water
Storage:	Frost-free
MAL Code:	(1993): 00-1
EU VOC Limit Value:	(Cat. A/d): 130g/l (2010). Contains max. 90g/l VOC.

This declaration applies to the colour white. The figures may vary for other colours.

DETAILS

Application:

Surfaces must be clean, dry, smooth and not transmit any loose particles. Glossy or rough surfaces must be sanded before painting. To prepare untreated/new wood sand the surface and seal knots with a suitable lacquer, apply primer then lightly sand to create a smooth surface. Finish with 2 coats of paint. To prepare previously painted wood, wash and sand the surfaces, fill cracks as needed finishing with a primer before applying 2 coats of paint. Stir the paint thoroughly before use. Drying time: approximately 12 hours at 23°C and 50% RH. Please follow full application instructions available at stleointeriors.com.

Coverage:

Approximately 8–10 M2/Litre.

Storage & Waste:

Always store in original packaging. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Storage temperature: Frost free. All paint residues and containers must be deposited at your local waste collection point.

CONTACT

+45 53740622

INFO@STLEOINTERIORS.COM

STLEOINTERIORS.COM