

St. Leo

DATA SHEET: MARBLE PAINT

PRODUCT DESCRIPTION:

Marble Paint merges the sensory quality of plaster with the deep colour profiles and effortless application of paint. When brushed or rolled onto interior walls and ceilings, Marble Paint imparts a subtle texture that is completely matte from all angles with a thick coverage and rich pigmentation to stand the test of time. Marble Paint is produced in Scandinavia from premium ingredients that are environmentally and health-conscious—the recipe is waterborne, solvent free and low-VOC. Offered in 16 colours plus custom hues, Marble Paint invites creativity within homes, retail and hospitality spaces as well as offices.

PHYSICAL / CHEMICAL DATA

Usage:	Interior walls and ceilings
Binder:	Copolymer dispersion
Gloss:	2 - matte
Drying time:	at 23 ° C / 50% RH: 3 hours. Recoat after 3 hours
Application Temp:	Min + 5°C. Max + 25°C
Humidity:	40-80% RH (65% RH optimal)
Tools:	Brush, roller
Contains:	Water. Max. 10%
Package Sizes:	10L, 100ML
Cleaning:	Water
Storage:	Frost-free
MAL Code:	(1993): 00-1
EU VOC Limit Value:	(cat. A/a): 30g/l (2010). Contains max. 1g/l VOC

DETAILS

Application:

Surfaces must be clean, dry, smooth and not transmit any loose particles. Prime untreated plaster, concrete and common construction boards before painting. Wash and degrease previously painted surfaces before painting. For best results apply 1-2 coats of primer before applying 2 coats of Marble Paint. Stir paint thoroughly before use.

Surface Dry: 3 hours with 50% RH at 23C. Ready to Repaint: 3 hours with 50% RH at 23C.

Coverage:

Approximately 4 – 6 M² / Litre (1 Layer)

Storage & Waste:

Always store in original packaging. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Storage temperature: Frost free. All paint residues and containers must be deposited at your local waste collection point.

CONTACT

+45 53740622

INFO@STLEOINTERIORS.COM

STLEOINTERIORS.COM